NSN 5305-01-318-9106

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-318-9106

| View Online at https://aerobasegroup.com/nsn/5305-01-318-9106 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.370 inches and 0.500 inches |
| Fastener Length: |
| Between 0.470 inches and 0.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.365 inches and 0.375 inches |
| Head Height: |
| Between 0.244 inches and 0.250 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.250 inches |
| Width Across Flats: |
| Between 0.187 inches and 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 33.0 rockwell c and 42.0 rockwell c |
| Minimum Yield Strength: |
| 120000 pounds per square inch |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416 type 2, cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unrc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| Shelf Life: |
| |

N/a

NSN 5305-01-318-9106

Socket Head Cap Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0