
NSN 5305-01-318-9112

Close Tolerance Screw - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.251 inches and 0.301 inches Fastener Length: Between 0.949 inches and 0.979 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1123 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-318-9112

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

