

View Online at <https://aerobasegroup.com/nsn/5305-01-319-0388>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.625 inches

**Fastener Length:**

1.625 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.729 inches and 0.750 inches

**Head Height:**

Between 0.302 inches and 0.312 inches

**Shoulder Diameter:**

0.496 inches first shoulder and 0.498 inches first shoulder

**Shoulder Length:**

1.000 inches first shoulder

**Hole Diameter:**

Between 0.061 inches and 0.067 inches

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.375 inches

**Width Across Flats:**

0.250 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

16

**Min. Tensile Strength (psi):**

140000 pounds per square inch

**Hardness Rating:**

32.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Round internal hexagon

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Surface Treatment:**

Zinc and chromate

**Surface Treatment Specification:**

Astm b633 type 2, cl 3 assn standard all treatment responses

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0