NSN 5305-01-319-1523

Socket Head Cap Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-319-1523



Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.220 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Thread Direction: Right-hand Thread Length: Between 0.220 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Right-hand Thread Length: Between 0.220 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Thread Length: Between 0.220 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Between 0.220 inches and 0.312 inches Fastener Length: Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Fastener Length:Between 0.282 inches and 0.312 inchesHead Style:ButtonHead Diameter:Between 0.250 inches and 0.262 inches
Between 0.282 inches and 0.312 inches Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Head Style: Button Head Diameter: Between 0.250 inches and 0.262 inches
Button Head Diameter: Between 0.250 inches and 0.262 inches
Head Diameter: Between 0.250 inches and 0.262 inches
Between 0.250 inches and 0.262 inches
Head Height:
Between 0.063 inches and 0.073 inches
Locking Feature:
Strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
0.078 inches
Thready Qty Per Inch (tpi):
32
Material:
Stainless steel fastener
Surface Treatment:
Passivate fastener
Thread Series Designator:
Unrc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0