NSN 5305-01-319-2207

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-319-2207

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.054 inches and 1.152 inches
Fastener Length:
Between 1.126 inches and 1.188 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.162 inches and 0.172 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1102 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-319-2207

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0