## NSN 5305-01-319-2422

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-319-2422

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.170 inches and 0.250 inches
Fastener Length:
Between 0.220 inches and 0.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Locking Feature:
Patch threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
Between 0.0937 inches and 0.0952 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b fastener
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener
Material Specification:
Astm a493 assn standard all material responses fastener
Surface Treatment:
Cadmium fastener
Surface Treatment Specification:
Qq-p-416 ty1 cl2 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:

80205-nas1352 professional/industrial association standard

## NSN 5305-01-319-2422

Socket Head Cap Screw - Page 2 of 2



				-
C I	20	lŧ.	l i	fe:
J.	16		_,	ıc.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0