NSN 5305-01-319-7277



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-319-7277 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 1.062 inches **Head Style:** Flat chamfer **Head Diameter:** 0.750 inches **Head Height:** 0.500 inches **First Diameter From Head:** 0.175 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Point Style:** Flat **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Criticality Code Justification: Externally Relieved Body Diameter Quantity: Special Features:** Straight knurl Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Special Test Features:**

Special quality control testing

Surface Treatment Specification:

Qq-p-35 type 1 federal specification single treatment response

NSN 5305-01-319-7277

Externally Relieved Body Screw - Page 2 of 2



Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Т	hr	ead	Seri	ies	Desi	ian	ator	٠.
•	•••	cau	OC!	163	Desi	y	atoi	

Unc

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0