NSN 5305-01-319-8556

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-319-8556 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.245 inches and 0.250 inches **Fastener Length:** Between 1.297 inches and 1.327 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.620 inches and 0.640 inches **Head Height:** Between 0.240 inches and 0.322 inches **First Diameter From Head:** Between 0.917 inches and 0.957 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm-a-581 assn standard single material response or astm-a-582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072-e300 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A003b0

NSN 5305-01-319-8556

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

Mil-f-14072-e300 spec.