NSN 5305-01-319-9289



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-319-9289 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.291 inches and 0.341 inches **Fastener Length:** Between 2.113 inches and 2.143 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.2481 inches and 0.2487 inches **Shank Unthreaded Hole Diameter:** 0.076 inches first hole and 0.086 inches first hole **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.802 inches and 1.822 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 1.987 inches first hole and 2.027 inches first hole Material: Titanium alloy uns r56400 **Material Specification:** Ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1154 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

--

NSN 5305-01-319-9289

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0