NSN 5305-01-320-0923

Thread Class:

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-320-0923

Thread Direction:
Right-hand
Thread Length:
Between 0.313 inches and 0.363 inches
Fastener Length:
Between 0.573 inches and 0.603 inches
Head Style:
Fillister
Head Diameter:
Between 0.306 inches and 0.313 inches
Head Height:
Between 0.103 inches and 0.118 inches
Locking Feature:
Strip threads
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.190 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
32.0 microinches threads
Material:
Plastic polychlorotrifluoroethylene locking feature
Material Specification:
Ams 5737 assn standard single material response fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unjf
Specification Data:
80205-nas1183 professional/industrial association standard

NSN 5305-01-320-0923

Close Tolerance Screw - Page 2 of 2



_			-	
C	hΔ	Iŧ.		ife:
•			_	IIC.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0