NSN 5305-01-320-0982

Machine Screw - Page 1 of 2

Between 1.001 inches and 1.125 inches

Thread Class:

Right-hand

Thread Length:

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-01-320-0982

Between 1.063 inches and 1.125 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Locking Feature:
Patch
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches

NSN 5305-01-320-0982

Machine Screw - Page 2 of 2

A500d0



Inread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia·