NSN 5305-01-320-0984

Machine Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-01-320-0984



3a **Thread Direction: Right-hand Thread Length:** Between 2.344 inches and 2.500 inches Fastener Length: Between 2.406 inches and 2.500 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Locking Feature: Patch **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Navy special project **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches Shank Surface Finish:

32.0 microinches

NSN 5305-01-320-0984

Machine Screw - Page 2 of 2



Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas1190 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0