

NSN 5305-01-320-3413 Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-320-3413 **Thread Class:** За **Thread Direction:** Right-hand

Thread Length: 1.750 inches **Fastener Length:** Between 1.940 inches and 2.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.937 inches **Head Height:** Between 0.616 inches and 0.625 inches **Hole Diameter:** 

Between 0.061 inches and 0.067 inches

**Internal Drive Style:** 

Hexagon

**Thread Diameter:** 

0.625 inches

Width Across Flats:

Between 0.500 inches and 0.505 inches

**Hole Quantity:** 

**Hole Type:** 

Drilled

Thready Qty Per Inch (tpi):

Min. Tensile Strength (psi):

170000 pounds per square inch

**Hardness Rating:** 

38.0 rockwell c and 45.0 rockwell c

Minimum Yield Strength:

150000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Steel

**Surface Treatment:** 

Cadmium and chromate

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5305-01-320-3413

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0