## NSN 5305-01-320-3654

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-320-3654

Thread Class:

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.245 inches and 0.312 inches
Fastener Length:
Between 0.281 inches and 0.312 inches
Head Style:
Pan
Head Diameter:
Between 0.155 inches and 0.167 inches
Head Height:
Between 0.053 inches and 0.062 inches
Locking Feature:
Strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polyamide
Screw Material Specification:
Ams5737 assn standard single material response
Screw Surface Treatment:
Passivate
Passivate  Screw Surface Treatment Specification:
Screw Surface Treatment Specification:
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unjc
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unjc  Specification Data:
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unjc  Specification Data:  80205-nas1190 professional/industrial association standard
Screw Surface Treatment Specification:  Qq-p-35 federal specification single treatment response  Thread Series Designator:  Unjc  Specification Data:  80205-nas1190 professional/industrial association standard  Shelf Life:

--

## NSN 5305-01-320-3654

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0