

View Online at <https://aerobasegroup.com/nsn/5305-01-320-4909>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.390 inches

Head Style:

Fillister

Head Diameter:

Between 0.380 inches and 0.420 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Material:

Steel comp 302 secondary washersteel comp 302 primary washer or steel comp 302b primary washer or steel comp 303 primary washer or steel comp 303 plus x primary washer or steel comp 303se primary washer or steel comp 303cu primary washer or steel comp 303ma primary washer or steel comp 304 primary washer or steel comp 304l primary washersteel comp 302 springsteel comp 303 stand-off or steel comp 303ma stand-off or steel comp 303pb stand-off or steel comp 303 plus x stand-off or steel comp 303se stand-off or steel comp 304 stand-offsteel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

Material Specification:

Mil-s-5059 military specification single material response secondary washerastm a313 assn standard single material response spring

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5059 spec.