NSN 5305-01-320-8836

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-320-8836 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.188 inches **Fastener Length:** 0.500 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.218 inches and 0.226 inches **Head Height:** Between 0.134 inches and 0.138 inches **First Diameter From Head:** Between 0.090 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.138 inches Width Across Flats: Between 0.109 inches and 0.111 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 **Material Specification:** 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

-

NSN 5305-01-320-8836

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0