

View Online at <https://aerobasegroup.com/nsn/5305-01-320-8838>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.203 inches

Fastener Length:

Between 0.343 inches and 0.375 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.338 inches and 0.348 inches

Washer Quantity:

2

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Secondary Washer Relationship To Primary Washer:

Not identical

Secondary Washer Style:

Flat

Primary Washer Outside Diameter:

0.334 inches

Secondary Washer Outside Diameter:

Between 0.338 inches and 0.348 inches

Primary Washer Style:

Split helical ring

Primary Washer Material Thickness:

Between 0.029 inches and 0.035 inches

Secondary Washer Material Thickness:

Between 0.029 inches and 0.035 inches

Material:

Steel comp 321 secondary washer or steel comp 347 secondary washer or steel comp 348 secondary washer

Material Specification:

Qq-s-763 cl 4 federal specification all material responses fastener or mil-s-7720 military specification 1st material response fastener

Thread Series Designator:

Unf

Specification Data:

80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6721 spec.