NSN 5305-01-320-8838

Assembled Washer Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-320-8838 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.203 inches **Fastener Length:** Between 0.343 inches and 0.375 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.338 inches and 0.348 inches Washer Quantity: **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 **Secondary Washer Relationship To Primary Washer:** Not identical **Secondary Washer Style:** Flat **Primary Washer Outside Diameter:** 0.334 inches **Secondary Washer Outside Diameter:** Between 0.338 inches and 0.348 inches **Primary Washer Style:** Split helical ring **Primary Washer Material Thickness:** Between 0.029 inches and 0.035 inches **Secondary Washer Material Thickness:** Between 0.029 inches and 0.035 inches Material: Steel comp 321 secondary washer or steel comp 347 secondary washer or steel comp 348 secondary washer **Material Specification:** Qq-s-763 cl 4 federal specification all material responses fastener or mil-s-7720 military specification 1st material response fastener

Unf

Thread Series Designator:

NSN 5305-01-320-8838

Assembled Washer Screw - Page 2 of 2



80205-nas1301 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6721 spec.