

View Online at <https://aerobasegroup.com/nsn/5305-01-321-2652>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.808 inches and 0.875 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Fillister

Head Diameter:

Between 0.124 inches and 0.140 inches

Head Height:

Between 0.070 inches and 0.083 inches

Internal Drive Style:

Slot

Thread Diameter:

0.086 inches

Thready Qty Per Inch (tpi):

56

Screw Material:

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-f-495 military specification single treatment response

Color:

Black

Thread Series Designator:

Unc

Specification Or Standard:

6 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-f-495 spec.