Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-3569

View Online at https://aerobasegroup.com/nsn/5305-01-321-3569
Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 1.272 inches and 1.312 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.1562 inches and 0.1587 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 32
32
32 Min. Tensile Strength (psi):
32 Min. Tensile Strength (psi): 160000 pounds per square inch
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material:
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Ion alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Marface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrf
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iorn alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Marface Treatment Specification (q-p-35 federal specification single treatment response Inread Series Designator: Unrf
32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:39.0 rockwell c and 45.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qr.p-35 federal specification single treatment responseIrnead Series Designator:UnrfSpecification Data:B0205-nas1351 professional/industrial association standard
32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qa-p-35 federal specification single treatment response Thread Series Designator: Unf Specification Data: 80205-nas1351 professional/industrial association standard
32Min. Tensile Strength (psi):160000 pounds per square inchHardness Rating:39.0 rockwell c and 45.0 rockwell cMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qr.p-35 federal specification single treatment responseIrnead Series Designator:UnrfSpecification Data:B0205-nas1351 professional/industrial association standard

NSN 5305-01-321-3569

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

