NSN 5305-01-321-3570

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-3570 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 2.250 inches **Fastener Length:** Between 10.985 inches and 11.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.293 inches and 1.312 inches **Head Height:** Between 0.864 inches and 0.875 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.875 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Precious Material And Location:** silver **Precious Material:** Silver **Surface Treatment:** Silver **Surface Treatment Specification:** Ams 2411 assn standard single treatment response **Thread Series Designator:**

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

NSN 5305-01-321-3570

Socket Head Cap Screw - Page 2 of 2



_				-		
C	h	Δ	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0