NSN 5305-01-321-3573

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-3573 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.211 inches and 0.281 inches **Fastener Length:** Between 0.524 inches and 0.597 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.344 inches and 0.406 inches **Head Height:** Between 0.156 inches and 0.219 inches **Shoulder Diameter:** 0.2485 inches first shoulder and 0.2495 inches first shoulder **Shoulder Length:** 0.313 inches first shoulder and 0.316 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.190 inches Width Across Flats: 0.125 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 303 or steel comp 304 **Material Specification:** Astm a582 assn standard 1st material response or astm a493 assn standard 2nd material response **Surface Treatment:**

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

NSN 5305-01-321-3573

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0