View Online at https://aerobasegroup.com/nsn/5305-01-321-4109

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.362 inches

Fastener Length:

Between 0.810 inches and 0.840 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.464 inches and 0.493 inches

Head Height:

Between 0.133 inches and 0.150 inches

Shoulder Diameter:

0.246 inches first shoulder and 0.249 inches first shoulder

Shoulder Length:

0.448 inches first shoulder and 0.458 inches first shoulder

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Shoulder Shape:

Round first shoulder

Material:

Steel comp 8630 or steel comp 4037

Material Specification:

Mil-s-6050 military specification 1st material response or ams 6300 assn standard 2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1298 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6050 spec.