NSN 5305-01-321-4111

Thread Class:

Thread Direction:

За

N/a

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-4111

Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 2.110 inches and 2.140 inches
Head Style:
Pan
Head Diameter:
Between 0.594 inches and 0.615 inches
Head Height:
Between 0.203 inches and 0.218 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.312 inches
Grip Length:
Between 1.740 inches and 1.760 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
Min. Tensile Strength (psi):
Min. Tensile Strength (psi): 160000 pounds per square inch
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 Material Specification: Ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf

NSN 5305-01-321-4111

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0