

View Online at <https://aerobasegroup.com/nsn/5305-01-321-4168>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

Between 1.261 inches and 1.291 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Special Features:

Drill shank hole, 0.107 in. Min, 0.127 in. Maximum lg from end; 0.070 in. Min, 0.080 maximum dia

Thread Series Designator:

Unjf

Specification Data:

80205-nas1633 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.