

View Online at <https://aerobasegroup.com/nsn/5305-01-321-6114>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

2.000 inches

**Fastener Length:**

Between 2.190 inches and 2.250 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 1.107 inches and 1.125 inches

**Head Height:**

Between 0.740 inches and 0.750 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.750 inches

**Width Across Flats:**

Between 0.625 inches and 0.631 inches

**Thready Qty Per Inch (tpi):**

10

**Min. Tensile Strength (psi):**

70000 pounds per square inch

**Hardness Rating:**

74.0 rockwell b fastener

**Minimum Yield Strength:**

26000 pounds per square inch

**Material:**

Steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener or steel comp xm-7 fastener

**Material Specification:**

Astm a493 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Astm a380 assn standard single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0