

View Online at <https://aerobasegroup.com/nsn/5305-01-321-6225>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.285 inches and 0.377 inches

Fastener Length:

Between 0.407 inches and 0.437 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.238 inches and 0.279 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

100.0 degrees

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Head Surface Treatment:

Paint

Screw Surface Treatment:

Passivate

Head Surface Treatment Specification:

595 no.36231 federal standard single treatment response or 330-1731-190 cage 13499 mfr ref single treatment response

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Color:

Gray

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0