## NSN 5305-01-321-6678

Close Tolerance Screw - Page 1 of 2

3a



**Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.313 inches and 0.363 inches Fastener Length: Between 1.011 inches and 1.041 inches **Head Style:** Fillister **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches Locking Feature: Strip threads **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches Grip Length: Between 0.678 inches and 0.698 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c fastener and 40.0 rockwell c fastener Surface Finish: 32.0 microinches threads Material: Plastic polychlorotrifluoroethylene locking feature **Material Specification:** Ams5737 assn standard single material response fastener **Surface Treatment:** Passivate fastener **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response fastener

## **Thread Series Designator:**

Unjf

32

## NSN 5305-01-321-6678

Close Tolerance Screw - Page 2 of 2



**Specification Data:** 

80205-nas1183 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0