NSN 5305-01-321-8734

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-8734 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.488 inches **Fastener Length:** Between 0.558 inches and 0.578 inches **Head Style:** Flat countersunk **Head Diameter:** 0.531 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.156 inches and 0.158 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 84.0 degrees Material: Steel **Material Specification:** 66 federal standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Dod-p-16232 ty m, cl 3 military specification single treatment response **Thread Series Designator:** Unrf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-321-8734

Socket Head Cap Screw - Page 2 of 2



_										
וו	0	m	ш	м	•	iza	31	^	n	

No

Fiig:

A003b0

Mil-std (military Standard):

spec.