## NSN 5305-01-321-9789

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-321-9789

Inread Class:
3a
Thread Direction:
Right-hand
Thread Length:
2.011 inches
Fastener Length:
Between 2.094 inches and 2.188 inches
Head Style:
Fillister
Head Diameter:
Between 0.429 inches and 0.438 inches
Head Height:
Between 0.162 inches and 0.183 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Specification Data:
80205-nas1101 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>

## NSN 5305-01-321-9789

Machine Screw - Page 2 of 2



em			

No

Fiig:

A500d0