

View Online at <https://aerobasegroup.com/nsn/5305-01-322-0041>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.683 inches and 0.750 inches

**Fastener Length:**

Between 0.719 inches and 0.750 inches

**Head Style:**

Fillister

**Head Diameter:**

0.140 inches

**Head Height:**

Between 0.070 inches and 0.083 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.086 inches

**Thready Qty Per Inch (tpi):**

56

**Screw Material:**

Copper alloy 268 or copper alloy 260 or copper alloy 230 or copper alloy 377 or copper alloy 360 or copper alloy 353 or copper alloy 270 or copper alloy 274 or copper alloy 462 or copper alloy 464 or copper alloy 482 or copper alloy 485 or copper alloy 510 or copper alloy 745 or copper alloy 752 or copper alloy 757 or copper alloy 764 or copper alloy 770 or copper alloy 240 or copper alloy 342

**Screw Surface Treatment:**

Oxide

**Screw Surface Treatment Specification:**

Mil-f-495 military specification single treatment response

**Color:**

Black

**Thread Series Designator:**

Unc

**Specification Or Standard:**

6 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-f-495 spec.