## NSN 5305-01-322-1593

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-1593

Thread Class:						
3a						
Thread Direction:						
Right-hand  Thread Length:						
2.500 inches						
Fastener Length:  Between 4.860 inches and 5.000 inches						
Head Style: Flat chamfer						
Head Diameter:						
Between 1.479 inches and 1.500 inches						
Head Height:						
Between 0.988 inches and 1.000 inches						
Locking Feature:						
_						
Patch threads or pellet threads or strip threads						
Internal Drive Style: Hexagon						
Thread Diameter:						
1.000 inches						
Width Across Flats:						
Between 0.7500 inches and 0.7570 inches  Thready Qty Per Inch (tpi):						
8						
Min. Tensile Strength (psi):						
170000 pounds per square inch						
Hardness Rating:						
38.0 rockwell c fastener and 45.0 rockwell c fastener						
Minimum Yield Strength:						
150000 pounds per square inch						
Material:						
Steel fastener						
Surface Treatment:						
Cadmium fastener and chromate fastener						
Surface Treatment Specification:						
Qq-p-416, type 2, class 2 federal specification single treatment response fastener						
Thread Series Designator:						
Unrc						
Specification Data:						
80205-nas1352 professional/industrial association standard						
Shelf Life:						

N/a

## NSN 5305-01-322-1593

Socket Head Cap Screw - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0