## NSN 5305-01-322-2548

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-2548 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.470 inches **Fastener Length:** 0.538 inches **Head Style:** Flat chamfer **Head Diameter:** 0.250 inches **Head Height:** 0.125 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.1406 inches and 0.1426 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Special Features:** Counterbore hole in threaded end, 2 spline cut outs longitudinally spaced 180.0 degrees opposite each other Color: Black Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-322-2548

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.