## NSN 5305-01-322-2549

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-2549 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.083 inches **Fastener Length:** Between 0.345 inches and 0.375 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.375 inches Width Across Flats: Between 0.313 inches and 0.316 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 39.0 rockwell c and 45.0 rockwell c **Hole Configuration Style:** Round internal hexagon Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Precious Material And Location:** silver **Precious Material:** 

Silver

## NSN 5305-01-322-2549

Socket Head Cap Screw - Page 2 of 2



Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2411 assn standard single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0