

View Online at <https://aerobasegroup.com/nsn/5305-01-322-2550>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.289 inches and 0.375 inches

Fastener Length:

Between 0.345 inches and 0.375 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.262 inches and 0.270 inches

Head Height:

Between 0.159 inches and 0.164 inches

Hole Diameter:

Between 0.044 inches and 0.050 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.164 inches

Width Across Flats:

Between 0.141 inches and 0.143 inches

Hole Quantity:

6

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

36

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 42.0 rockwell c

Minimum Yield Strength:

120000 pounds per square inch

Hole Configuration Style:

Round internal hexagon

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5737 assn standard single material response

Precious Material And Location:

silver

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams2411 assn standard single treatment response

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0