NSN 5305-01-322-2947

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-2947 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.528 inches and 0.620 inches **Fastener Length:** Between 0.590 inches and 0.620 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams5731 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 63.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc **Specification Data:** 80205-nas8103 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-322-2947

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0