NSN 5305-01-322-3174

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-3174 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.323 inches **Fastener Length:** Between 0.496 inches and 0.526 inches **Head Style:** Pan **Head Diameter:** Between 0.306 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Grip Diameter:** Between 0.1625 inches and 0.1635 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.164 inches **Grip Length:** Between 0.178 inches and 0.198 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard 2nd material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas7702 professional/industrial association standard Shelf Life: N/a

No

Unit Of Measure:

Demilitarization:

NSN 5305-01-322-3174

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.