NSN 5305-01-322-3603

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-3603

Through Olegan
Thread Class:
3a ————————————————————————————————————
Thread Direction:
Right-hand
Thread Length:
Between 0.348 inches and 0.440 inches
Fastener Length:
Between 0.410 inches and 0.440 inches
Head Style:
Round extended washer
Head Diameter:
Between 0.343 inches and 0.363 inches
Head Height:
Between 0.086 inches and 0.106 inches
Extended Washer Diameter:
Between 0.413 inches and 0.443 inches
Extended Washer Thickness:
Between 0.030 inches and 0.037 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Screw Material:
Iron alloy 660
Screw Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas8403 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-322-3603

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0