NSN 5305-01-322-4712

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-4712

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.387 inches and 0.500 inches |
| Fastener Length: |
| Between 0.470 inches and 0.500 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| Between 0.303 inches and 0.312 inches |
| Head Height: |
| Between 0.185 inches and 0.190 inches |
| Internal Drive Style: |
| Hexagon |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| Between 0.156 inches and 0.159 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 80000 pounds per square inch |
| Hardness Rating: |
| 80.0 rockwell b |
| Minimum Yield Strength: |
| 30000 pounds per square inch |
| Material: |
| Steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7 |
| Material Specification: |
| Astm a493 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416 ty1 cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unrc |
| Specification Data: |
| 80205-nas1352 professional/industrial association standard |
| Shelf Life: |
| |

N/a

NSN 5305-01-322-4712

Socket Head Cap Screw - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0