3a

14

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-322-4713



Thread Class: Thread Direction: Right-hand Thread Length: 2.250 inches **Fastener Length:** Between 5.485 inches and 5.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 1.293 inches and 1.312 inches **Head Height:** Between 0.864 inches and 0.875 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.875 inches Width Across Flats: Between 0.750 inches and 0.757 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Precious Material And Location:** silver **Precious Material:** Silver Surface Treatment: Silver **Surface Treatment Specification:** Ams 2411 assn standard single treatment response **Thread Series Designator:** Unrf **Specification Data:**

80205-nas1351 professional/industrial association standard

NSN 5305-01-322-4713

Socket Head Cap Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

