NSN 5305-01-322-5058

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-5058 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.715 inches and 0.745 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.285 inches and 0.315 inches **Head Height:** Between 0.096 inches and 0.116 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.188 inches and 0.250 inches **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.125 inches and 0.127 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp 304 stand-off **Material Specification:** Qq-s-763 federal specification single material response stand-off or mil-s-23195 military specification single material response stand-off or ams 5639 assn standard single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life:

Unit Of Measure: Demilitarization: No Fiig: A003b0

N/a

NSN 5305-01-322-5058

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.