Socket Head Cap Screw - Page 1 of 2

Ams 2411 assn standard single treatment response



response

View Online at https://aerobasegroup.com/nsn/5305-01-322-6041

Thread Class:	
За	
Thread Direction:	
Right-hand	
Thread Length:	
1.250 inches	
Fastener Length:	
Between 1.585 inches and 1.625 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.550 inches and 0.562 inches	
Head Height:	
Between 0.368 inches and 0.375 inches	
Hole Diameter:	
Between 0.061 inches and 0.067 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.375 inches	
Width Across Flats:	
Between 0.312 inches and 0.316 inches	
Hole Quantity:	
6	
Ноје Туре:	
Drilled	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Hardness Rating:	
33.0 rockwell c and 42.0 rockwell c	
Minimum Yield Strength:	
120000 pounds per square inch	
Hole Configuration Style:	
Round longitudinal hole	
Material:	
Iron alloy 660	
Material Specification:	
Ams 5731 assn standard single material response or ams 5737 assn standard single mate	rial
Surface Treatment Specification:	
Ame 2411 even standard single treatment reasoned	

## NSN 5305-01-322-6041

Socket Head Cap Screw - Page 2 of 2



**Thread Series Designator:** 

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0