NSN 5305-01-322-6972

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-6972 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** 1.500 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.609 inches and 0.641 inches **Head Height:** Between 0.672 inches and 0.704 inches **First Diameter From Head:** Between 0.225 inches and 0.235 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.875 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity:** Color: Black Material: Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se **Material Specification:** Astm a582 assn standard all material responses **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 military specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5305-01-322-6972

Externally Relieved Body Screw - Page 2 of 2



Unit	Of	Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.