Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-322-6972

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.365 inches and 0.375 inches
Fastener Length:
1.500 inches
Head Style:
Knurled no. 5
Head Diameter:
Between 0.609 inches and 0.641 inches
Head Height:
Between 0.672 inches and 0.704 inches
First Diameter From Head:
Between 0.225 inches and 0.235 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.875 inches
Point Style:
Cone
Internal Drive Style:
Slot
Thread Diameter:
0.312 inches
Thready Qty Per Inch (tpi):
18
Externally Relieved Body Diameter Quantity:
1
Color:
Black
Material:
Steel comp 303 or steel comp 303ma or steel comp 303pb or steel comp 303 plus x or steel comp 303se
Material Specification:
Astm a582 assn standard all material responses
Surface Treatment:
Oxide
Surface Treatment Specification:
Mil-c-13924 military specification single treatment response
Thread Series Designator:
Unc
Shelf Life:

N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.