Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-6974

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Fastener Length:	
2.500 inches	
Head Style:	
Flat chamfer	
Head Diameter:	
Between 0.729 inch	ies and 0.750 inches
Head Height:	
Between 0.302 inch	ies and 0.312 inches
Locking Feature:	
Pellet threads or stri	ip threads or patch threads
Thread Diameter:	
0.500 inches	
Thready Qty Per In	ıch (tpi):
13	
Min. Tensile Streng	gth (psi):
80000 pounds per s	quare inch
Hardness Rating:	
33.0 rockwell c and	d 42.0 rockwell c
Criticality Code Ju	stification:
Zzzy	
Material:	
Steel comp 302 or s	steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7
Surface Treatment	:
Passivate	
Special Test Featu	ires:
Special quality contr	rol testing
Test Data Docume	nt:
81349-mil-p-23199 s	specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes co	ommercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and p	performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Desi	ignator:
Unc	
Departure From Ci	ited Document:

Departure From Cited Document:

As modified by material and locking feature

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-322-6974

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

