NSN 5305-01-322-7395

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-7395 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.216 inches and 0.347 inches **Fastener Length:** Between 0.469 inches and 0.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.452 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 62000 pounds per square inch **Countersink Angle:** Between 80.0 degrees and 82.0 degrees **Screw Material:** Aluminum alloy 2024 **Screw Material Specification:** Qq-a-225/6 federal specification single material response **Screw Surface Treatment:** Anodize **Screw Surface Treatment Specification:** Mil-a-8625 ty1 cl1 military specification single treatment response **Thread Series Designator:** Unc **Specification Or Standard:** 3 type and 2c style Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

Fiig:

A500d0

NSN 5305-01-322-7395

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-a-8625 spec.