## NSN 5305-01-322-8850

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-322-8850

Thread Class:		
3a		
Thread Direction:		
Right-hand		
Thread Length:		
Between 0.507 inches and 0.590 inches		
Fastener Length:		
Between 0.719 inches and 0.750 inches		
Head Style:		
Flat countersunk		
Head Diameter:		
Between 0.742 inches and 0.762 inches		
Locking Feature:		
Patch or pellet or strip		
Internal Drive Style:		
Cross recess type 1		
Thread Diameter:		
0.375 inches		
Thready Qty Per Inch (tpi):		
24		
Countersink Angle:		
Between 99.0 degrees and 101.0 degrees		
Screw Material:		
Iron alloy 660		
Locking Feature Material:		
Plastic polyamide		
Screw Material Specification:		
Ams 5737 assn standard single material response		
Screw Surface Treatment:		
Passivate		
Screw Surface Treatment Specification:		
Qq-p-35 federal specification single treatment response		
Bearing Surface Of Head Surface Finish:		
32.0 microinches		
Shank Surface Finish:		
32.0 microinches		
Thread Surface Finish:		
32.0 microinches		
Thread Series Designator:		
Unjf		
Specification Data:		
80205-nas1189 professional/industrial association standard		

## NSN 5305-01-322-8850

Machine Screw - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A500d0