## NSN 5305-01-323-0223

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-323-0223 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.156 inches and 0.218 inches **Fastener Length:** Between 0.781 inches and 0.846 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.281 inches and 0.343 inches **Head Height:** Between 0.125 inches and 0.187 inches **Shoulder Diameter:** 0.186 inches first shoulder and 0.187 inches first shoulder **Shoulder Length:** 0.625 inches first shoulder and 0.628 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Hardness Rating: 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1 federal specification single treatment response **Thread Series Designator:** Unc

Shelf Life:

N/a

## NSN 5305-01-323-0223

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0