

View Online at <https://aerobasegroup.com/nsn/5305-01-323-3108>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.626 inches

**Fastener Length:**

Between 2.361 inches and 2.391 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.848 inches and 0.925 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.625 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

99.0 degrees and 101.0 degrees

**Screw Material:**

Titanium alloy uns r56400

**Screw Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response

**Bearing Surface Of Head Surface Finish:**

32.0 microinches

**Shank Surface Finish:**

32.0 microinches

**Thread Surface Finish:**

32.0 microinches

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas4910 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0