## NSN 5305-01-323-3108

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-323-3108

| Thread Class:  |
|--|
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.626 inches   |
| Fastener Length:   |
| Between 2.361 inches and 2.391 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.848 inches and 0.925 inches  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.625 inches   |
| Thready Qty Per Inch (tpi):  |
| 18   |
| Min. Tensile Strength (psi):   |
| 160000 pounds per square inch  |
| Countersink Angle:   |
| 99.0 degrees and 101.0 degrees   |
| Screw Material:  |
| Titanium alloy uns r56400  |
| Screw Material Specification:  |
| Ams4928 assn standard single material response or ams4967 assn standard single material response |
| Screw Surface Treatment:   |
| Cadmium and chromate   |
| Screw Surface Treatment Specification:   |
| Qq-p-416, ty2 cl2 federal specification single treatment response                                |
| Bearing Surface Of Head Surface Finish:  |
| 32.0 microinches   |
| Shank Surface Finish:  |
| 32.0 microinches   |
| Thread Surface Finish:   |
| 32.0 microinches   |
| Thread Series Designator:  |
| Unjf   |
| Specification Data:  |
| 80205-nas4910 professional/industrial association standard                                       |
| Shelf Life:  |

N/a

## NSN 5305-01-323-3108

Machine Screw - Page 2 of 2



|  |  |  | ure: |  |
|--|--|--|------|--|
|  |  |  |      |  |
|  |  |  |      |  |

--

Demilitarization:

No

Fiig:

A500d0